

Kit Ref	Polyglass							
	130 V	136 V	165 V	165 V3	260 V3	27 V	33 V	38 V
Woofer	5 V1	5 V2	6 V1	6 V1	10 V1	27 V	33 V	38 V
Mid Range				4 V1	5 V2			
Tweeter	TN 45	TN 45	TN 45	TN 45	TMC Ti			
Crossover	FA V1	FA V1	FA V1	FA V2	FA V3			
Fs (Hz)	74.9	74.9	74.7	74.7	49.7	26.5	25.2	20.1
Re (ohms)	3.1	3.1	2.8	2.8	3.1	2.6	2.6	3.0
Qes	0.65	0.46	0.79	0.79	0.94	0.43	0.5	0.43
Qms	7.78	6.78	9.24	9.24	6.53	14.13	13.39	17.2
Qts	0.60	0.43	0.73	0.73	0.82	0.42	0.48	0.42
Dia (cm)	10.5	10.5	13	13	21	20.5	26	33
Mms (g)	8.0	7.1	10.5	10.5	40.7	108.6	122.3	162.2
Lvc (mH)	0.32	0.27	0.38	0.38	0.56	1.55	1.8	1.23
Hbob (mm)	11	11	14.5	14.5	17	32	32	24
Hgap (mm)	5	5	5	5	6	8	8	10
Xmax (mm)	3	3	4.75	4.75	5.5	12	12	7
Sd (cm2)	86.6	86.6	132.7	132.7	346.4	330.1	530.9	855.3
Vas (l)	5.9	6.7	10.7	10.7	42.5	50.8	128.8	399.0
BL (N/A)	4.3	4.7	4.2	4.2	6.5	10.4	10.1	11.9
Folding dia.	115	116	142	142	233	233	288	397
Mounting depth (mm)	63	66	69	69	97	132	158	163.5
Sealed enclosure (l.)						10-30	20-40	50-200
Bass reflex enclosure (l.)								